



## Quantum® Gold Pro

Prep for Card | Coin Drop Installed

#### Built for Reliable Performance

Speed Queen's stack washer/dryer brings an innovative stacked concept that takes up half the floor space that a conventional washer and dryer does when situated side by side. The freestanding softmount design can be installed on all floor types or levels. Both washer and dryer have the same hookups and connections as a standard washer and dryer. No additional plumbing or electrical change is needed. Speed Queen's stack washer/dryer combines heavy-duty construction with reliable operation proven to stand the test of time. They're designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. Front load products have met every design standard to be 100% ADA compliant.





- · Integrated meter case
- · Large capacity meter case standard
- Wash Alert™ capability

#### Washer (ADA Compliant)

- · Rugged suspension system
- Industry leading 1200 RPM spin speed exerts 440 G-force extraction
- · Durable stainless steel washtub
- · Four-compartment soap dispenser
- Extra-wide 15.5" door opening and 180° door swing

#### Dryer

- · Upfront lint filter easy to clean
- Industry's largest door opening 2.06 sq. ft. (1914 cm2)
- Quiet, efficient blower system




#### Quantum® Gold Pro Control

The Quantum® Gold Pro control delivers a truly premium experience to residents. From intuitive soft touch buttons that walk them through cycle options to multiple actuations (coin, card, mobile) for payment flexibility, this control gives residents the wash and dry options they want, and the revenue potential managers desire.

# Stack Washer/Dryer – Short

### Quantum® Gold Pro

Control Option         Quantum Gold Pro           Color         White           Capacity - Ib (kg)         Washer 21.5 (9.5)           Dryer         18 (8.2)           Overall Width - in (mm)         26.875 (683)           Overall Depth - in (mm)         27.73 (704)           Overall Height - in (mm)         76.5 (1943)           Cylinder Volume cu. ft. (liters)         Washer 20 (198)           Cu. ft. (liters)         0.9 (0.67)           Type Of Gas (Gas Models Only)         Natural gas           Water Consumption Per Cycle - g (liter)**         13.68 (51.78)           IWF (Water Factor) - gal/ft³ (liters/kiter/cycle)**         4.0 (0.53)           MEF, (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**         2.20 (62.3)           Available Water Temperatures         Hot, Warm, Cold           Available Cycles         Dryer         High, Medium, Low, Delicate           Available Cycles         Dryer         High, Medium, Low, Delicate           Air Outlet Diameter - in (mm)         4 (102)           Exhaust Airflow - cfm (liters/sec)         220 (105)           Electrical Requirements         Gas         25,000 Btu           Net Weight - Ib (kg)         385 (175)           Shipping Dimensions Approx in (mm)         Width Approx in (mm)	Specifications				
Capacity - Ib (kg)	Control Option	Quantum Gold Pro			
Overall Width - in (mm) Overall Depth - in (mm) Overall Depth - in (mm) Overall Height - in (mm)  Cylinder Volume cu. ft. (liters) Dryer Overall Motor Size - HP (kW)  Motor Size - HP (kW)  Type Of Gas (Gas Models Only) Water Consumption Per Cycle - g (liter)**  IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**  MEF <sub>1</sub> (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Washer Available Cycles  Dryer  Air Outlet Diameter - in (mm)  Electrical Requirements  Requirements  Electric Requirement  Gas  Electric Gas Shipping Weight - lb (kg)  Shipping Dimensions Approx in (mm)  Agency Approvals  Possible Washer  Available Cycles  Dryer  Bish, Medium, Low, Delicate, No Heat  Alt (102)  Electric 120/208-240/60/1-30 amp  Electric 5350W, 240V  4750W, 208V  4750W, 208V  4750W, 208V  Augency Approvals  Electric CULus  Electric CULus	Color	White			
Overall Width - in (mm)         26.875 (683)           Overall Depth - in (mm)         27.73 (704)           Overall Height - in (mm)         76.5 (1943)           Cylinder Volume cu. ft. (liters)         Washer Dryer           Cu. ft. (liters)         0.9 (0.67)           Motor Size - HP (kW)         0.9 (0.67)           Type Of Gas (Gas Models Only)         Natural gas           Water Consumption Per Cycle - g (liter)**         13.68 (51.78)           IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**         4.0 (0.53)           MEF (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**         2.20 (62.3)           Available Water Temperatures         Hot, Warm, Cold           Washer         Normal, Synthetic, Delicate           Available Cycles         Dryer         High, Medium, Low, Delicate, No Heat           Air Outlet Diameter - in (mm)         4 (102)           Exhaust Airflow - cfm (liters/sec)         220 (105)           Electrical Requirements         Electric           Gas         120/208-240/60/1-30 amp           Heating Element         Gas           Met Weight - Ib (kg)         385 (175)           Shipping Weight - Ib (kg)         417 (189)           Shipping Dimensions Approx in (mm)         Width August           Agency Approvals </td <td>Capacity - lb (kg)</td> <td colspan="2">21.5 (9.5)</td>	Capacity - lb (kg)	21.5 (9.5)			
Overall Depth - in (mm)  Overall Height - in (mm)  Cylinder Volume Cu. ft. (liters)  Motor Size - HP (kW)  Type Of Gas (Gas Models Only)  Water Consumption Per Cycle - g (liter)**  IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**  MEF_ (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Washer  Available Cycles  Dryer  High, Medlum, Low, Delicate, No Heat  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas  Lectric Bectric Gas Siow, 240/4750W, 208V 4750W, 208V 4750W, 208V Shipping Weight - lb (kg)  Shipping Dimensions Approx in (mm)  Agency Approvals  Electric Cyles  Pryer  High, Medlum, Low, Delicate 120/208-240/60/1-30 amp 120/60/1-15 amp  Electric S350W, 240V 4750W, 208V 4750W, 208V 4750W, 208V Bethe Add Add Add Add Add Add Add Add Add Ad		18 (8.2)			
Overall Height - in (mm)  Cylinder Volume cu. ft. (liters)  Dryer  70. (198)  Motor Size - HP (kW)  Type Of Gas (Gas Models Only)  Water Consumption Per Cycle - g (liter)**  IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**  MEF. (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Washer  Available Cycles  Dryer  High, Medlum, Low, Delicate, No Heat  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas  Lectrical Requirements  Electric  Electric  Gas  Lectric S350W, 240/4750W, 208V  Gas S5,000 Btu  Net Weight - lb (kg)  Shipping Weight - lb (kg)  Shipping Dimensions Approx in (mm)  Agency Approvals  Electric  Electric CULus  Washer  A.0 (0.53)  L.0 (62.8)  A.0 (0.53)  A2.0 (62.8)  A2.0 (62.3)  A2.0 (62.8)  A2.0 (62	Overall Width - in (mm)		26.875 (683)		
Cylinder Volume cu. ft. (liters)  Dryer  7.0 (198)  Motor Size - HP (kW)  Type Of Gas (Gas Models Only)  Water Consumption Per Cycle - g (liter)**  IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**  MEF_ (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Washer Available Cycles  Dryer  High, Medium, Low, Delicate, No Heat  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas 120/60/1-15 amp  Electric S350W, 240V 4750W, 208V Gas 25,000 Btu  Net Weight - lb (kg)  Shipping Weight - lb (kg)  Shipping Dimensions Approx in (mm)  Agency Approvals  Washer  A.0 (0.53)  Havaria gas  4.0 (0.53)  Hot, Warm, Cold  Not Warm, Cold  Hot, Warm, Cold  12.20 (62.3)	Overall Depth - in (mm)	27.73 (704)			
Cú. ft. (liters)Dryer7.0 (198)Motor Size - HP (kW)0.9 (0.67)Type Of Gas (Gas Models Only)Natural gasWater Consumption Per Cycle - g (liter)**13.68 (51.78)IWF (Water Factor) - gal/ft3 (liters/liter/cycle)**4.0 (0.53)MEF, (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**2.20 (62.3)Available Water TemperaturesHot, Warm, ColdAvailable CyclesDryerHigh, Medium, Low, Delicate, No HeatAir Outlet Diameter - in (mm)4 (102)Exhaust Airflow - cfm (liters/sec)220 (105)Electrical RequirementsElectric Gas120/208-240/60/1-30 amp 120/60/1-15 ampHeating ElementElectric Gas5350W, 240V 4750W, 208V 25,000 BtuNet Weight - Ib (kg)385 (175)Shipping Weight - Ib (kg)Width 417 (189)Shipping Dimensions Approx in (mm)Depth Height 80 (2032)Agency ApprovalsElectric CULus	Overall Height - in (mm)	76.5 (1943)			
Motor Size - HP (kW)  Type Of Gas (Gas Models Only)  Water Consumption Per Cycle - g (liter)**  IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**  MEF, (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Washer  Available Cycles  Dryer  Washer  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas  Electric 220 (62.3)  Electrical Requirements  Flectric 320/208-240/60/1-30 amp  Electric 4750W, 208V  Gas 25,000 Btu  Net Weight - Ib (kg)  Shipping Weight - Ib (kg)  Shipping Dimensions Approx in (mm)  Agency Approvals  Electric cULus		Washer	3.42 (96.8)		
Type Of Gas (Gas Models Only)  Water Consumption Per Cycle - g (liter)**  IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**  MEF, (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Hot, Warm, Cold  Washer  Available Cycles  Dryer  High, Medium, Low, Delicate, No Heat  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas  Electric Requirements  Gas  Electric Gas  S350W, 240V 4750W, 208V Gas 25,000 Btu  Net Weight - Ib (kg)  Shipping Weight - Ib (kg)  Shipping Dimensions Approx in (mm)  Agency Approvals  Electric  Electric CULus  Natural gas  13.68 (51.78)  13.68 (51.78)  4.0 (0.53)  12.0 (62.3)  Flect 2.20 (62.3)  Flectric COLUS	cu. ft. (liters)	Dryer	7.0 (198)		
Water Consumption Per Cycle - g (liter)**  IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**  MEF_ (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Washer  Available Cycles  Dryer  High, Medium, Low, Delicate, No Heat  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas  Electric  Requirement  Electric  Gas  S350W, 240V 4750W, 208V 4750W, 208V Gas  Shipping Weight - lb (kg)  Shipping Weight - lb (kg)  Shipping Dimensions Approx in (mm)  Agency Approvals  Flectric  Langle Gas  13.68 (51.78)  4.0 (0.53)  Lect. (0.53)  Elect. (2.20 (62.3)  Hot, Warm, Cold  Normal, Synthetic, Delicate  Normal, Synthetic, Delicate  120/208-240/60/1-30 amp  120/208-240/60/1-30 amp  120/60/1-15 amp  Flectric  S350W, 240V 4750W, 208V 4750W, 208V 4750W, 208V 4750W, 208V 4750W, 208V 4760W, 208V 4760W, 208V 4760W, 208V 477 (189)  Flectric  Agency Approvals	Motor Size - HP (kW)	0.9 (0.67)			
IWF (Water Factor) - gal/ft3	Type Of Gas (Gas Models 0	Natural gas			
MEF_ (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)**  Available Water Temperatures  Washer Normal, Synthetic, Delicate  Dryer High, Medium, Low, Delicate, No Heat  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas 120/60/1-15 amp  Electric Gas 25,000 Btu  Net Weight - lb (kg)  Shipping Weight - lb (kg)  Shipping Dimensions Approx in (mm)  Masher Normal, Synthetic, Delicate  Normal, Synthetic, Delicate  100/208-240/60/1  120/208-240/60/1-30 amp  120/60/1-15 amp  Electric 5350W, 240V  4750W, 208V  25,000 Btu  385 (175)  Width 34 (864)  Depth 30 (762)  Height 80 (2032)  Electric CULus	Water Consumption Per Cyc (liter)**	13.68 (51.78)			
Available Water Temperatures  Available Water Temperatures  Available Cycles  Dryer  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Heating Element  Net Weight - Ib (kg)  Shipping Weight - Ib (kg)  Shipping Dimensions Approx in (mm)  Available Water Temperatures  Hot, Warm, Cold  Normal, Synthetic, Delicate  High, Medium, Low, Delicate  4 (102)  220 (105)  Electric  Gas 120/208-240/60/1-30 amp  Electric  5350W, 240V  4750W, 208V  25,000 Btu  417 (189)  Width 34 (864)  Depth 30 (762)  Height 80 (2032)  Electric  Agency Approvals	IWF (Water Factor) - gal/ft³ (liters/liter/cycle)**	4.0 (0.53)			
Available Cycles  Dryer  High, Medium, Low, Delicate, No Heat  Air Outlet Diameter - in (mm)  Exhaust Airflow - cfm (liters/sec)  Electrical Requirements  Gas 120/60/1-15 amp  Heating Element  Flectric Gas 25,000 Btu  Net Weight - Ib (kg)  Shipping Weight - Ib (kg)  Shipping Dimensions Approx in (mm)  Masher  Normal, Synthetic, Delicate  High, Medium, Low, Delicate, No Heat  Heating Element  520 (105)  Electric 5350W, 240V 4750W, 208V 4750W, 208V 4750W, 208V 4750W, 208V 475 (189)  Width 34 (864) 30 (762) Height 80 (2032)  Electric CULus	MEF. (Modified Energy Fac ft³/kWh/cycle (Liters/kWh/	2.20 (62.3)			
Available Cycles  Dryer High, Medium, Low, Delicate, No Heat  Air Outlet Diameter - in (mm) 4 (102)  Exhaust Airflow - cfm (liters/sec) 220 (105)  Electrical Requirements Gas 120/60/1-15 amp  Heating Element Electric 5350W, 240V 4750W, 208V 25,000 Btu  Net Weight - lb (kg) 385 (175)  Shipping Weight - lb (kg) 417 (189)  Shipping Dimensions Approx in (mm) Depth 30 (762) Height 80 (2032)  Electric CULus	Available Water Temperatu	ures	Hot, Warm, Cold		
Dryer   High, Medium, Low, Delicate, No Heat			Normal, Synthetic, Delicate		
Exhaust Airflow - cfm (liters/sec)         220 (105)           Electrical Requirements         Electric Gas         120/208-240/60/1-30 amp           Heating Element         5350W, 240V 4750W, 208V 25,000 Btu           Net Weight - Ib (kg)         385 (175)           Shipping Weight - Ib (kg)         417 (189)           Shipping Dimensions Approx in (mm)         Width 34 (864) Depth 30 (762) Height 80 (2032)           Agency Approvals         Electric	Available Cycles	Dryer			
Electrical Requirements         Electric Gas         120/208-240/60/1-30 amp           Heating Element         Electric Gas         5350W, 240V 4750W, 208V           Heating Element         Gas         25,000 Btu           Net Weight - Ib (kg)         385 (175)           Shipping Weight - Ib (kg)         417 (189)           Shipping Dimensions Approx in (mm)         Depth 30 (762) Height 80 (2032)           Agency Approvals         Electric	Air Outlet Diameter - in (m	m)	4 (102)		
Heating Element   Electric   5350W, 240V   4750W, 208V   Gas   25,000 Btu	Exhaust Airflow - cfm (liter	rs/sec)	220 (105)		
Heating Element   Electric   5350W, 240V   4750W, 208V   25,000 Btu	Electrical	Electric	120/208-240/60/1-30 amp		
Heating Element   Gas   25,000 Btu		Gas	120/60/1-15 amp		
Gas   25,000 Btu	Heating Element	Electric			
Shipping Weight - Ib (kg)  Width 34 (864)  Shipping Dimensions Approx in (mm)  Agency Approvals  Width 30 (762)  Height 80 (2032)  Electric cULus		Gas	25,000 Btu		
(kg)  Width 34 (864)  Shipping Dimensions Approx in (mm)  Depth 30 (762)  Height 80 (2032)  Electric cULus	Net Weight - lb (kg)	385 (175)			
Shipping Dimensions Approx in (mm)  Depth 30 (762)  Height 80 (2032)  Electric cULus			417 (189)		
Approx in (mm)  Height 80 (2032)  Agency Approvals  Electric cULus		Width	34 (864)		
Height 80 (2032)  Electric cULus  Agency Approvals		Depth	30 (762)		
Agency Approvals	. I. I	Height	80 (2032)		
Agency Approvals  Gas cCSAus	A	cULus			
	Agency Approvals Ga		cCSAus		



Α.	Overall Width - in (mm)	26.875 (683)
В.	Overall Depth - in (mm)	27.73 (704)
C.	Overall Height - in (mm)	76.5 (1943)
D.	Floor To Door Opening -in (mm)	14.5 (368)*
E.	Door Swing - in (mm)	23.5 (597)

<sup>\*</sup> For ADA compliance turn legs out from base 0.5 inches

Models	Voltage/Freq	/PH	Drain	Actuation
STENCFSP176TW01	208-240/60/1	Electric	Pump	Coin I
STGNCFSP116TW01	120/60/1	Gas	Pump	Installed
STENYFSP176TW01	208-240/60/1	Electric	Pump	Prep for
STGNYFSP116TW01	120/60/1	Gas	Pump	Card

Electric dryers come equipped for 208-240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit.

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

Commercial product is not authorized for sale to Residential end consumers.

<sup>\*\*</sup> Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.