

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		1777.3 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	360.0V x 180.0H
	At 50% of Imax	360.0V x 180.0H
	At 90% of Imax	360.0V x 180.0H
Beam Flux	Total	1000.1 lumens per klm.
	To 10% of Imax	539.2 lumens per klm.
	To 50% of Imax	345.5 lumens per klm.
	To 90% of Imax	29.7 lumens per klm.
	Upward LOR	10.9 %
	Downward LOR	89.1 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-07-22

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.14V I:0.4110A P:3.515W PF:0.7042 Freq:59.97Hz Lamp Flux:2.99222x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Micro	WEIGHT:
SPEC.:3.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:LAB-047+LAB-161



DATA OF LAMP		Eff:0.85lm/W	
MODEL	M4B1-3.5W-30K-40-A	Imax(cd)	5.318
NOMINAL POWER(W)	3.5	AVAILABILITY(%)	53.1
RATED VOLTAGE(V)	12	Avai. FLUX(lm)	1.588
NOMINAL FLUX(lm)	2.99222	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	2.992
TEST VOLTAGE(V)	12	θ @50%(H,V)	180,360DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.05	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	0.00
70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.00
60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.19	0.09
50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.37	0.31
40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.20	0.15
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.16	0.12
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.14	0.11
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.14	0.11
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.16	0.12
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.21	0.16
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.38	0.32
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.18	0.10
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.00	0.02	0.04	0.08	0.16	0.38	0.25	0.22	0.21	0.21	0.22	0.24	0.35	0.15	0.07	0.04	0.02	0.00	3	---
Φ a	0.00	0.00	0.00	0.00	0.06	0.30	0.18	0.15	0.14	0.14	0.14	0.16	0.26	0.06	0.00	0.00	0.00	0.00	---	2

one-half-peak spread: U:39.0,D:38.0 , L:57.5,R:58.5


NEMA Beam Type: Type 7

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-07-22

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.14V I:0.4110A P:3.515W PF:0.7042 Freq:59.97Hz Lamp Flux:2.99222x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Micro	WEIGHT:
SPEC.:3.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:LAB-047+LAB-161




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-07-22

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.14V I:0.4110A P:3.515W PF:0.7042 Freq:59.97Hz Lamp Flux:2.99222x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Micro	WEIGHT:
SPEC.:3.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:LAB-047+LAB-161



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-07-22

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-07-22

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.14V I:0.4110A P:3.515W PF:0.7042 Freq:59.97Hz Lamp Flux:2.99222x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Micro	WEIGHT:
SPEC.:3.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:LAB-047+LAB-161



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-07-22

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.14V I:0.4110A P:3.515W PF:0.7042 Freq:59.97Hz Lamp Flux:2.99222x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Micro	WEIGHT:
SPEC.:3.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:LAB-047+LAB-161

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.01	0.00	0.01	0.01	0.00	0.04	0.07	0.11	0.16	0.16	0.17	0.13	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-170	0.01	0.00	0.01	0.01	0.00	0.03	0.07	0.11	0.16	0.16	0.16	0.14	0.01	0.00	0.00	0.00	0.00	0.00	0.00
-160	0.01	0.00	0.01	0.00	0.00	0.02	0.07	0.10	0.15	0.16	0.16	0.16	0.12	0.01	0.00	0.00	0.00	0.00	0.00
-150	0.01	0.01	0.01	0.00	0.00	0.01	0.04	0.07	0.10	0.16	0.16	0.16	0.15	0.15	0.11	0.06	0.01	0.00	0.00
-140	0.01	0.01	0.00	0.00	0.01	0.00	0.02	0.04	0.07	0.10	0.13	0.16	0.16	0.16	0.16	0.15	0.14	0.14	0.13
-130	0.01	0.01	0.00	0.01	0.00	0.00	0.00	0.01	0.03	0.07	0.08	0.09	0.10	0.12	0.15	0.16	0.15	0.15	0.15
-120	0.01	0.01	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.02	0.03	0.05	0.07	0.08	0.09	0.09	0.09	0.09
-110	0.01	0.01	0.01	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.01	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.01	0.02	0.01	0.02	0.06	0.11	0.12	0.13	0.13	0.15	0.14	0.14	0.14	0.14	0.15	0.17	0.18	0.19	0.19
-70	0.01	0.01	0.06	0.12	0.14	0.14	0.16	0.18	0.19	0.20	0.21	0.23	0.25	0.25	0.25	0.24	0.23	0.23	0.23
-60	0.01	0.02	0.12	0.15	0.15	0.17	0.19	0.22	0.21	0.18	0.25	0.30	0.31	0.32	0.35	0.37	0.39	0.40	0.41
-50	0.01	0.05	0.14	0.15	0.16	0.19	0.20	0.18	0.30	0.31	0.35	0.37	0.44	0.37	0.36	0.52	0.58	0.58	0.58
-40	0.01	0.11	0.15	0.15	0.18	0.19	0.23	0.30	0.33	0.41	0.30	0.55	0.55	0.51	0.75	1.53	2.96	3.90	4.17
-30	0.01	0.12	0.14	0.15	0.21	0.16	0.29	0.32	0.44	0.42	0.54	0.62	2.64	3.62	0.50	0.22	0.56	0.06	0.00
-20	0.01	0.12	0.14	0.16	0.19	0.27	0.31	0.39	0.28	0.53	0.76	4.83	0.58	0.65	0.05	0.00	0.00	0.00	0.00
-10	0.01	0.12	0.14	0.16	0.14	0.29	0.30	0.41	0.54	0.49	3.34	0.74	0.50	0.01	0.00	0.00	0.00	0.00	0.00
0	0.01	0.12	0.14	0.16	0.12	0.30	0.30	0.34	0.52	0.59	4.88	0.59	0.00	0.00	0.00	0.00	0.00	0.00	0.00
10	0.01	0.12	0.14	0.16	0.14	0.29	0.30	0.39	0.53	0.49	3.52	0.75	0.41	0.00	0.00	0.00	0.00	0.00	0.00
20	0.01	0.12	0.14	0.15	0.18	0.27	0.30	0.37	0.29	0.50	0.78	4.91	0.61	0.40	0.00	0.00	0.00	0.00	0.00
30	0.01	0.12	0.15	0.15	0.20	0.16	0.29	0.30	0.41	0.42	0.49	0.65	3.24	2.86	0.54	0.23	0.15	0.00	0.00
40	0.01	0.11	0.15	0.15	0.16	0.17	0.22	0.29	0.30	0.37	0.21	0.50	0.47	0.50	0.82	2.31	4.12	4.72	4.90
50	0.01	0.05	0.14	0.15	0.15	0.16	0.17	0.17	0.29	0.30	0.30	0.32	0.36	0.23	0.40	0.47	0.47	0.48	0.48
60	0.01	0.02	0.13	0.15	0.15	0.15	0.16	0.18	0.17	0.15	0.24	0.29	0.29	0.30	0.30	0.29	0.30	0.31	0.32
70	0.01	0.01	0.07	0.13	0.15	0.15	0.15	0.15	0.16	0.16	0.16	0.17	0.18	0.18	0.15	0.13	0.12	0.12	0.12
80	0.01	0.02	0.02	0.03	0.08	0.13	0.13	0.13	0.15	0.16	0.16	0.16	0.16	0.16	0.17	0.17	0.17	0.17	0.17
90	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.01	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.01	0.01	0.01	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.01	0.01	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.07	0.07	0.08	0.08	0.09
130	0.01	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.02	0.03	0.07	0.10	0.11	0.12	0.15	0.16	0.16	0.16	0.16
140	0.01	0.01	0.00	0.00	0.01	0.00	0.01	0.03	0.07	0.10	0.12	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16
150	0.01	0.01	0.01	0.00	0.00	0.00	0.03	0.07	0.11	0.16	0.16	0.16	0.16	0.16	0.13	0.11	0.06	0.05	0.06
160	0.01	0.00	0.01	0.00	0.00	0.02	0.07	0.10	0.15	0.16	0.16	0.17	0.13	0.04	0.01	0.00	0.00	0.00	0.00
170	0.01	0.00	0.01	0.01	0.00	0.03	0.07	0.11	0.16	0.16	0.16	0.14	0.02	0.00	0.00	0.00	0.00	0.00	0.00
180	0.01	0.00	0.01	0.01	0.00	0.04	0.07	0.11	0.16	0.16	0.17	0.13	0.00	0.00	0.00	0.00	0.00	0.00	0.00

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ADMIN
 Test Date:2023-07-22

V(B) Range:-180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
 Humidity:65.0%
 Test Distance:13.563m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.14V I:0.4110A P:3.515W PF:0.7042 Freq:59.97Hz Lamp Flux:2.99222x1 lm																	
NAME: LED LANDSCAPE LIGHT									TYPE:Micro						WEIGHT:		
SPEC.:3.5W 3000K 40°LENS									DIM.:						SERIAL No.:1		
MFR.: EVERFINE									SUR.:						Shielding Angle:LAB-047+LAB-161		

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.06	0.11	0.14	0.15	0.14	0.11	0.04	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.00	0.00	0.00	0.00	0.00	0.06	0.13	0.15	0.15	0.14	0.10	0.04	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.00	0.00	0.00	0.00	0.04	0.11	0.14	0.15	0.15	0.14	0.09	0.03	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.01	0.02	0.06	0.10	0.14	0.15	0.15	0.15	0.14	0.09	0.05	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.13	0.14	0.15	0.15	0.15	0.15	0.14	0.13	0.10	0.05	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.15	0.15	0.15	0.14	0.12	0.10	0.08	0.06	0.04	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.08	0.08	0.08	0.07	0.06	0.04	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.19	0.18	0.16	0.15	0.14	0.13	0.13	0.13	0.13	0.11	0.10	0.10	0.08	0.06	0.04	0.03	0.01	0.00	
-70	0.23	0.23	0.23	0.24	0.23	0.22	0.22	0.21	0.20	0.19	0.18	0.15	0.12	0.11	0.09	0.06	0.03	0.00	
-60	0.40	0.38	0.36	0.34	0.30	0.28	0.27	0.25	0.16	0.19	0.19	0.18	0.18	0.14	0.12	0.09	0.05	0.00	
-50	0.57	0.56	0.50	0.38	0.37	0.37	0.35	0.32	0.28	0.25	0.20	0.17	0.17	0.17	0.14	0.11	0.06	0.00	
-40	3.91	3.03	1.65	0.77	0.49	0.47	0.49	0.33	0.34	0.30	0.25	0.23	0.16	0.16	0.16	0.12	0.07	0.00	
-30	0.06	0.58	0.27	0.31	3.22	2.88	0.64	0.42	0.43	0.32	0.29	0.24	0.17	0.16	0.16	0.13	0.08	0.00	
-20	0.00	0.00	0.00	0.05	0.74	0.27	4.61	0.82	0.39	0.35	0.30	0.26	0.23	0.15	0.15	0.13	0.08	0.00	
-10	0.00	0.00	0.00	0.00	0.01	0.60	0.32	3.69	0.46	0.42	0.28	0.26	0.22	0.13	0.15	0.14	0.09	0.00	
0	0.00	0.00	0.00	0.00	0.00	0.00	0.16	4.89	0.60	0.36	0.26	0.26	0.22	0.11	0.14	0.13	0.09	0.00	
10	0.00	0.00	0.00	0.00	0.00	0.51	0.33	3.87	0.46	0.41	0.27	0.25	0.22	0.12	0.14	0.13	0.09	0.00	
20	0.00	0.00	0.00	0.00	0.50	0.29	4.69	0.84	0.36	0.37	0.29	0.25	0.23	0.14	0.14	0.14	0.08	0.00	
30	0.00	0.18	0.28	0.35	2.45	3.49	0.66	0.37	0.43	0.28	0.27	0.24	0.16	0.15	0.15	0.13	0.08	0.00	
40	4.73	4.19	2.43	0.84	0.48	0.39	0.44	0.24	0.30	0.27	0.25	0.22	0.14	0.15	0.15	0.12	0.08	0.00	
50	0.47	0.46	0.46	0.43	0.23	0.29	0.30	0.27	0.27	0.25	0.19	0.14	0.15	0.16	0.14	0.11	0.06	0.00	
60	0.31	0.29	0.28	0.28	0.28	0.27	0.26	0.24	0.14	0.14	0.15	0.15	0.16	0.14	0.12	0.09	0.05	0.00	
70	0.12	0.12	0.13	0.14	0.16	0.16	0.15	0.15	0.15	0.16	0.16	0.15	0.13	0.12	0.09	0.07	0.03	0.00	
80	0.17	0.17	0.17	0.16	0.16	0.16	0.15	0.15	0.14	0.12	0.11	0.10	0.09	0.08	0.06	0.03	0.01	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.08	0.08	0.07	0.06	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.16	0.16	0.16	0.15	0.12	0.10	0.09	0.06	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.16	0.16	0.16	0.16	0.16	0.16	0.15	0.12	0.10	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.06	0.07	0.10	0.12	0.16	0.16	0.16	0.15	0.14	0.09	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.00	0.00	0.00	0.01	0.07	0.12	0.15	0.16	0.15	0.14	0.09	0.03	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.00	0.00	0.00	0.00	0.00	0.07	0.13	0.15	0.15	0.14	0.10	0.04	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.00	0.00	0.00	0.00	0.00	0.06	0.11	0.14	0.15	0.14	0.11	0.04	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-07-22

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks: