


N7B1-2.5W-30-A



PROJECT: _____

TYPE: _____

CAT #: _____

DESCRIPTION

Nano, LumienPRO - TW, Brass - Antique, 1.95in, 2.5W, 121-132 Lm, 2700-5700K, 30°, 10-15V

SPECIFICATIONS

Construction	Brass
Finish	Antique
Lead Wire	6'
Voltage	10-15V
Light Warranty	10 Years

FINISHES



Antique

NOTES

Lumien Lighting

770-485-9002
orders@lumienlighting.com
www.lumienlighting.com

Lumien Lighting reserves the right to modify product specifications without notification. © 2023 Lumien Enterprise Inc.

MODULE TYPE (required)	WATTS	COLOR TEMP	BEAM SPREAD	FINISH	ACCESSORIES
---------------------------	-------	---------------	----------------	--------	-------------

N7B1-2.5W-30-A



CORE: N4B1

- - - -

1.5W 3000K 15° A
2.5W 2700K 30°



N7B1-2.5W-30-A



CORE: N4B2

- - - -

2W 2700K 30° A
3000K



N7B1-2.5W-30-A



PRO: N7B1

- - - -

2.5W 2700-5700K 15° A
30° BK



N7B1-2.5W-30-A



PRO: N8B1

- - - -

2.5W 2700-5700K 30° A
BK



	CORE	CORE	CORE	PRO
	N4B1-1.5W-27K-15-A N4B1-1.5W-27K-30-A N4B1-1.5W-30K-15-A N4B1-1.5W-30K-30-A	N4B1-2.5W-27K-15-A N4B1-2.5W-27K-30-A N4B1-2.5W-30K-15-A N4B1-2.5W-30K-30-A	N4B2-2W-27K-30-A N4B2-2W-30K-30-A	N7B1-2.5W-15-BK N7B1-2.5W-30-A N7B1-2.5W-30-BK
Construction	Brass	Brass	Brass	Brass
Finish	Antique	Antique	Antique	Antique, Black
Input Voltage	10-15V	10-15V	10-15V	10-15V
Wattage (Volt Amps)	1.5W (2.56)	2.5W (3.97)	2W (3.21)	2.5W (4.02)
Module Lumens	100 Lm, 141 Lm, 113 Lm,	163 Lm, 217 Lm, 172 Lm,	203 Lm, 209 Lm	200 Lm, 121-132 Lm
Color Temperature	2700K, 3000K	2700K, 3000K	2700K, 3000K	2700-5700K
Beam Spread	15°, 30°	15°, 30°	30°	15°, 30°
Lead Wire Length	6'	6'	6'	6'
CRI	80+	80+	80+	80+
RGB	No	No	No	No
Dimmable	Primary Dimming	Primary Dimming	Primary Dimming	With LumienPRO Remote
Rated Life	50,000 Hrs	50,000 Hrs	50,000 Hrs	50,000 Hrs
Warranty	10 Years	10 Years	10 Years	10 Years
Core Drill Size	-	-	-	-

PRO

N8B1-2.5W-27K-30-A
N8B1-2.5W-27K-30-BK
N8B1-2.5W-30K-30-A
N8B1-2.5W-30K-30-BK

Construction	Brass
Finish	Antique, Black
Input Voltage	10-15V
Wattage (Volt Amps)	2.5W (4.02)
Module Lumens	27K: 91 Lm, R: 29 Lm, G:
Color Temperature	2700-5700K
Beam Spread	30°
Lead Wire Length	6'
CRI	80+
RGB	Yes
Dimmable	With LumienPRO Remote
Rated Life	50,000 Hrs
Warranty	10 Years
Core Drill Size	-