

Floodlight Summary:

Report based on lamp delivering 1000 lumens.


Maximum Intensity		1011.7 cd per klm.
(Luminaire orientation as tested.)		0.0 degrees vertical
		0.0 degrees horizontal
Beam Spread	At 10% of Imax	72.7V x 136.6H
	At 50% of Imax	45.9V x 83.8H
	At 90% of Imax	13.7V x 33.5H
Beam Flux	Total	1000.0 lumens per klm.
	To 10% of Imax	955.1 lumens per klm.
	To 50% of Imax	638.4 lumens per klm.
	To 90% of Imax	150.3 lumens per klm.
	Upward LOR	0.0 %
	Downward LOR	100.0 %
Luminaire Efficiency(Light Output Ratio)		100.0 %

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-10

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.15V I:0.6933A P:5.620W PF:0.6673 Freq:59.98Hz Lamp Flux:35.943x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Step Light	WEIGHT:
SPEC.:6W 3000K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:6.40lm/W	
MODEL	S3A5-6W-30K-BZ	Imax (cd)	36.36
NOMINAL POWER (W)	6W	AVAILABILITY (%)	95.7
RATED VOLTAGE (V)	12	Avai. FLUX (lm)	34.40
NOMINAL FLUX (lm)	35.943	LOR (%)	100.0
LAMPS INSIDE	1	TOTAL FLUX (lm)	35.94
TEST VOLTAGE (V)	12	θ @50% (H,V)	84,46DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00
90	0.00	0.00	0.00	0.01	0.04	0.08	0.11	0.13	0.12	0.12	0.13	0.11	0.08	0.04	0.01	0.00	0.00	0.00	1.00	0.65
80	0.00	0.00	0.01	0.07	0.24	0.39	0.50	0.61	0.69	0.69	0.60	0.49	0.38	0.23	0.07	0.01	0.00	0.00	5.01	4.94
70	0.00	0.00	0.04	0.18	0.38	0.55	0.70	0.87	1.01	1.01	0.86	0.69	0.54	0.37	0.17	0.04	0.00	0.00	7.42	7.39
60	0.00	0.00	0.07	0.21	0.36	0.52	0.65	0.77	0.89	0.89	0.77	0.64	0.50	0.35	0.20	0.07	0.00	0.00	6.90	6.87
50	0.00	0.01	0.08	0.19	0.30	0.42	0.54	0.62	0.69	0.69	0.62	0.53	0.41	0.29	0.18	0.07	0.01	0.00	5.64	5.61
40	0.00	0.01	0.07	0.14	0.23	0.32	0.44	0.52	0.56	0.56	0.51	0.43	0.31	0.22	0.14	0.06	0.01	0.00	4.53	4.50
30	0.00	0.01	0.05	0.09	0.15	0.22	0.31	0.40	0.44	0.44	0.40	0.30	0.21	0.14	0.09	0.04	0.01	0.00	3.30	3.23
20	0.00	0.00	0.02	0.04	0.07	0.10	0.14	0.19	0.22	0.22	0.19	0.14	0.10	0.06	0.04	0.02	0.00	0.00	1.54	1.22
10	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.04	0.02	0.02	0.04	0.04	0.03	0.02	0.01	0.00	0.00	0.00	0.33	0.00
0	0.00	0.00	0.00	0.01	0.02	0.02	0.02	0.01	0.00	0.00	0.00	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.14	0.00
-10	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.06	0.00
-20	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90 -80 -70 -60 -50 -40 -30 -20 HORIZONTAL (DEG) 20 30 40 50 60 70 80 90																				
Φ t	0.00	0.04	0.34	0.98	1.83	2.67	3.46	4.15	4.65	4.64	4.12	3.41	2.60	1.76	0.94	0.32	0.03	0.00	36	---
Φ a	0.00	0.00	0.23	0.87	1.70	2.54	3.34	4.06	4.59	4.58	4.03	3.30	2.47	1.64	0.84	0.22	0.00	0.00	---	34


one-half-peak spread: U:37.1,D:9.4 , L:18.2,R:38.2 CEMA Beam Type: Type 7 x 5 (H x V)

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-10

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.15V I:0.6933A P:5.620W PF:0.6673 Freq:59.98Hz Lamp Flux:35.943x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Step Light	WEIGHT:
SPEC.:6W 3000K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-10

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.15V I:0.6933A P:5.620W PF:0.6673 Freq:59.98Hz Lamp Flux:35.943x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Step Light	WEIGHT:
SPEC.:6W 3000K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-10

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-10

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.15V I:0.6933A P:5.620W PF:0.6673 Freq:59.98Hz Lamp Flux:35.943x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Step Light	WEIGHT:
SPEC.:6W 3000K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2023-10-10

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.15V I:0.6933A P:5.620W PF:0.6673 Freq:59.98Hz Lamp Flux:35.943x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Step Light	WEIGHT:
SPEC.:6W 3000K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.05	0.05	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-50	0.00	0.00	0.00	0.00	0.00	0.08	0.11	0.12	0.12	0.08	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-40	0.00	0.00	0.00	0.00	0.09	0.16	0.20	0.21	0.22	0.20	0.14	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-30	0.00	0.00	0.00	0.00	0.13	0.23	0.29	0.34	0.38	0.37	0.33	0.25	0.12	0.00	0.00	0.00	0.00	0.00	0.00
-20	0.00	0.00	0.00	0.08	0.20	0.34	0.40	0.52	0.58	0.62	0.62	0.59	0.51	0.34	0.07	0.00	0.00	0.00	0.00
-10	0.00	0.00	0.00	0.11	0.26	0.40	0.51	0.66	0.79	0.91	1.02	1.06	1.10	1.08	0.91	0.60	0.02	0.00	0.00
0	0.00	0.00	0.00	0.12	0.29	0.45	0.60	0.77	1.03	1.20	1.39	1.66	1.81	1.98	2.13	2.29	2.37	2.43	2.43
10	0.00	0.00	0.06	0.48	1.54	2.58	3.23	3.87	4.49	4.94	5.64	6.38	7.27	8.29	9.37	10.5	11.6	11.3	12.0
20	0.00	0.00	0.10	0.61	2.51	4.53	5.71	6.84	7.89	8.67	9.54	10.8	12.2	13.7	15.5	16.1	16.3	16.8	17.7
30	0.00	0.00	0.11	0.49	2.86	5.61	7.84	9.50	11.0	12.4	13.5	14.6	16.3	17.8	18.5	19.0	19.6	20.3	21.2
40	0.00	0.00	0.08	0.48	2.23	5.65	9.21	11.6	13.7	15.5	17.4	19.1	20.2	21.2	22.5	23.7	24.9	26.2	27.7
50	0.00	0.00	0.04	0.36	0.96	3.83	7.85	11.8	15.5	17.8	20.2	22.0	23.6	25.2	27.0	28.7	30.5	32.4	34.4
60	0.00	0.00	0.01	0.14	0.59	1.23	3.32	7.47	11.7	15.8	19.9	21.4	22.3	23.8	25.8	27.9	30.1	32.3	34.1
70	0.00	0.00	0.01	0.02	0.13	0.43	0.96	1.59	2.36	4.18	7.01	8.63	9.61	9.92	10.2	10.5	10.8	10.7	10.3
80	0.00	0.00	0.00	0.01	0.02	0.03	0.04	0.09	0.21	0.38	0.51	0.62	0.74	0.80	0.84	0.84	0.81	0.74	0.65
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

H(β) Range:-90 - 90DEG
 H(β) Interval: 0.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ADMIN
 Test Date:2023-10-10

V(B) Range:-180 - 180DEG
 V(B) Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
 Humidity:65.0%
 Test Distance:13.563m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.15V I:0.6933A P:5.620W PF:0.6673 Freq:59.98Hz Lamp Flux:35.943x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Step Light	WEIGHT:
SPEC.:6W 3000K	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.05	0.06	0.06	0.03	0.00	0.00	0.00	0.00	0.00	0.00	
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.11	0.15	0.15	0.13	0.10	0.04	0.00	0.00	0.00	0.00	0.00	
-30	0.00	0.00	0.00	0.00	0.00	0.10	0.21	0.27	0.29	0.28	0.24	0.18	0.10	0.02	0.00	0.00	0.00	0.00	
-20	0.00	0.00	0.00	0.07	0.30	0.45	0.52	0.53	0.50	0.44	0.37	0.27	0.17	0.05	0.00	0.00	0.00	0.00	
-10	0.00	0.02	0.56	0.84	0.97	0.99	0.95	0.86	0.76	0.64	0.50	0.36	0.22	0.09	0.00	0.00	0.00	0.00	
0	2.40	2.32	2.19	2.03	1.84	1.64	1.44	1.22	1.00	0.81	0.60	0.43	0.26	0.11	0.00	0.00	0.00	0.00	
10	11.4	11.7	10.4	9.29	8.15	7.11	6.22	5.42	4.70	4.22	3.62	2.99	2.31	1.34	0.39	0.06	0.00	0.00	
20	16.8	16.3	16.1	15.4	13.6	12.0	10.6	9.32	8.33	7.55	6.48	5.40	4.25	2.31	0.57	0.10	0.00	0.00	
30	20.3	19.5	18.9	18.3	17.6	16.1	14.3	13.1	12.0	10.6	9.09	7.48	5.40	2.75	0.49	0.12	0.01	0.00	
40	26.1	24.9	23.6	22.3	20.9	19.7	18.6	16.8	15.0	13.2	11.1	8.95	5.42	2.20	0.47	0.10	0.01	0.00	
50	32.3	30.3	28.5	26.7	24.8	23.0	21.4	19.5	17.2	14.9	11.6	7.62	3.82	0.95	0.37	0.06	0.01	0.00	
60	32.2	30.0	27.6	25.4	23.4	21.7	20.7	19.5	15.5	11.5	7.47	3.45	1.21	0.60	0.18	0.03	0.01	0.00	
70	10.7	10.7	10.4	10.0	9.79	9.59	8.73	7.20	4.50	2.33	1.58	0.97	0.49	0.18	0.04	0.02	0.00	0.00	
80	0.74	0.81	0.84	0.85	0.83	0.80	0.72	0.64	0.51	0.30	0.16	0.09	0.07	0.05	0.02	0.01	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEGH(β) Interval: 0.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:ADMIN

Test Date:2023-10-10

V(B) Range:-180 - 180DEG

V(B) Interval: 0.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352

Humidity:65.0%

Test Distance:13.563m [K=1.0000]

Remarks: