

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	228.3 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	360.0V x 180.0H
	At 50% of Imax	360.0V x 180.0H
	At 90% of Imax	360.0V x 180.0H

Beam Flux	Total	999.9 lumens per klm.
	To 10% of Imax	974.9 lumens per klm.
	To 50% of Imax	566.1 lumens per klm.
	To 90% of Imax	117.9 lumens per klm.

Upward LOR	69.8 %
Downward LOR	30.2 %


Luminaire Efficiency(Light Output Ratio)	100.0 %
--	---------

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.18V I:0.6883A P:5.324W PF:0.6349 Freq:59.97Hz Lamp Flux:32.1753x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Path Light	WEIGHT:
SPEC.:5.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:6.04lm/W	
MODEL	A2A2-BK	Imax (cd)	7.346
NOMINAL POWER (W)	5.5	AVAILABILITY (%)	97.5
RATED VOLTAGE (V)	12	Avai. FLUX (lm)	31.36
NOMINAL FLUX (lm)	32.1753	LOR (%)	100.0
LAMPS INSIDE	1	TOTAL FLUX (lm)	32.18
TEST VOLTAGE (V)	12	θ @50% (H,V)	180,360DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.07	0.00
90	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.24	0.15
80	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.04	0.05	0.05	0.04	0.03	0.03	0.02	0.01	0.01	0.00	0.00	0.39	0.35
70	0.00	0.00	0.01	0.02	0.03	0.04	0.06	0.07	0.07	0.07	0.06	0.06	0.04	0.03	0.02	0.01	0.00	0.00	0.59	0.57
60	0.00	0.00	0.01	0.02	0.04	0.06	0.07	0.08	0.08	0.08	0.07	0.07	0.06	0.04	0.02	0.01	0.00	0.00	0.72	0.70
50	0.00	0.00	0.01	0.03	0.05	0.06	0.07	0.08	0.08	0.08	0.08	0.07	0.06	0.05	0.03	0.01	0.00	0.00	0.77	0.77
40	0.00	0.01	0.02	0.04	0.05	0.07	0.07	0.06	0.06	0.06	0.06	0.07	0.06	0.05	0.03	0.01	0.01	0.00	0.73	0.72
30	0.00	0.01	0.02	0.04	0.05	0.06	0.06	0.05	0.04	0.04	0.05	0.06	0.06	0.05	0.04	0.02	0.01	0.00	0.66	0.65
	0.00	0.01	0.02	0.04	0.05	0.06	0.05	0.04	0.01	0.02	0.05	0.06	0.06	0.05	0.04	0.02	0.01	0.00	0.57	0.55
	0.00	0.01	0.02	0.04	0.05	0.06	0.06	0.04	0.01	0.02	0.05	0.06	0.06	0.05	0.04	0.02	0.01	0.00	0.58	0.55
	0.00	0.01	0.02	0.04	0.05	0.06	0.06	0.05	0.04	0.05	0.06	0.06	0.06	0.05	0.04	0.02	0.01	0.00	0.67	0.67
	0.00	0.01	0.02	0.04	0.05	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.06	0.05	0.03	0.02	0.01	0.00	0.76	0.75
-30	0.00	0.00	0.01	0.03	0.05	0.07	0.08	0.08	0.08	0.08	0.08	0.07	0.06	0.05	0.03	0.01	0.01	0.00	0.80	0.80
-40	0.00	0.00	0.01	0.03	0.04	0.06	0.07	0.08	0.09	0.09	0.08	0.07	0.06	0.04	0.02	0.01	0.00	0.00	0.77	0.76
-50	0.00	0.00	0.01	0.02	0.03	0.05	0.06	0.07	0.08	0.08	0.07	0.06	0.05	0.03	0.02	0.01	0.00	0.00	0.64	0.63
-60	0.00	0.00	0.01	0.01	0.02	0.03	0.04	0.05	0.05	0.05	0.05	0.04	0.03	0.02	0.01	0.01	0.00	0.00	0.44	0.42
-70	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.26	0.18
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.01	0.06	0.20	0.42	0.64	0.83	0.92	0.93	0.89	0.90	0.95	0.91	0.80	0.62	0.40	0.19	0.07	0.01	10	---
Φ a	0.00	0.02	0.16	0.38	0.61	0.80	0.89	0.90	0.85	0.87	0.93	0.89	0.78	0.59	0.37	0.16	0.02	0.00	---	9

one-half-peak spread: U:38.0,D:36.0 , L:36.0,R:46.0


NEMA Beam Type: Type 7

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.18V I:0.6883A P:5.324W PF:0.6349 Freq:59.97Hz Lamp Flux:32.1753x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Path Light	WEIGHT:
SPEC.:5.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.18V I:0.6883A P:5.324W PF:0.6349 Freq:59.97Hz Lamp Flux:32.1753x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Path Light	WEIGHT:
SPEC.:5.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.18V I:0.6883A P:5.324W PF:0.6349 Freq:59.97Hz Lamp Flux:32.1753x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Path Light	WEIGHT:
SPEC.:5.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.18V I:0.6883A P:5.324W PF:0.6349 Freq:59.97Hz Lamp Flux:32.1753x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Path Light	WEIGHT:
SPEC.:5.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-180	0.00	0.64	0.86	1.19	1.89	3.24	4.51	5.16	5.94	6.89	7.22	6.53	6.14	5.38	4.28	3.06	1.69	0.00	0.00
-170	0.00	0.63	0.86	1.17	1.86	3.22	4.46	5.13	5.87	6.45	7.30	6.66	6.27	5.91	4.86	3.89	2.78	1.89	1.51
-160	0.00	0.58	0.84	1.10	1.70	3.10	4.01	4.92	5.61	6.15	6.86	7.10	6.67	6.35	6.05	5.58	4.97	4.62	4.54
-150	0.00	0.52	0.80	1.07	1.46	2.45	3.54	4.63	5.18	5.80	6.21	6.86	7.16	7.07	6.74	6.59	6.45	6.34	6.30
-140	0.00	0.38	0.74	0.97	1.26	1.79	2.90	3.71	4.66	5.11	5.63	6.07	6.30	6.56	6.85	7.00	7.05	7.04	7.03
-130	0.00	0.12	0.63	0.88	1.09	1.35	1.79	2.59	3.36	4.02	4.78	5.13	5.45	5.78	6.08	6.25	6.35	6.41	6.45
-120	0.00	0.03	0.64	0.74	0.91	1.09	1.25	1.51	1.86	2.36	3.00	3.42	3.83	4.22	4.59	4.95	5.10	5.19	5.25
-110	0.00	0.01	0.24	0.64	0.68	0.84	0.95	1.04	1.18	1.28	1.42	1.58	1.73	1.88	2.04	2.18	2.30	2.39	2.44
-100	0.00	0.00	0.02	0.09	0.30	0.53	0.65	0.65	0.70	0.78	0.85	0.92	0.98	1.03	1.07	1.09	1.12	1.14	1.16
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.02	0.09	0.27	0.32	0.35	0.38	0.42	0.46	0.51	0.55	0.59	0.63	0.66	0.69	0.71
-70	0.00	0.00	0.02	0.28	0.34	0.40	0.53	0.59	0.70	0.80	0.89	1.03	1.11	1.21	1.26	1.33	1.39	1.44	1.47
-60	0.00	0.00	0.27	0.34	0.50	0.60	0.73	0.93	1.09	1.27	1.41	1.58	1.73	1.88	1.99	2.06	2.15	2.21	2.26
-50	0.00	0.01	0.32	0.46	0.61	0.80	1.03	1.27	1.52	1.78	1.97	2.25	2.43	2.53	2.60	2.66	2.72	2.76	2.80
-40	0.00	0.03	0.33	0.51	0.70	1.00	1.28	1.62	1.90	2.26	2.45	2.53	2.65	2.71	2.82	2.87	2.90	2.92	2.95
-30	0.00	0.12	0.39	0.59	0.86	1.18	1.54	1.88	2.32	2.44	2.56	2.65	2.78	2.74	2.66	2.56	2.50	2.47	2.48
-20	0.00	0.20	0.43	0.61	0.94	1.32	1.75	2.15	2.38	2.51	2.67	2.70	2.59	2.41	2.22	2.06	1.89	1.81	1.82
-10	0.00	0.26	0.45	0.61	1.03	1.41	1.78	2.30	2.37	2.48	2.66	2.57	2.34	2.09	1.83	1.52	1.16	0.85	0.78
0	0.00	0.28	0.46	0.60	1.06	1.41	1.81	2.30	2.33	2.46	2.61	2.48	2.23	1.96	1.62	1.14	0.55	0.00	0.00
10	0.00	0.26	0.45	0.61	1.02	1.39	1.77	2.28	2.34	2.46	2.65	2.56	2.30	2.05	1.80	1.48	1.13	0.86	0.75
20	0.00	0.21	0.43	0.60	0.92	1.28	1.71	2.11	2.32	2.44	2.61	2.68	2.56	2.32	2.12	1.98	1.82	1.78	1.79
30	0.00	0.12	0.39	0.59	0.83	1.13	1.48	1.84	2.26	2.34	2.46	2.57	2.73	2.69	2.61	2.44	2.34	2.30	2.31
40	0.00	0.04	0.33	0.51	0.67	0.95	1.21	1.54	1.83	2.16	2.33	2.38	2.48	2.56	2.68	2.75	2.83	2.86	2.89
50	0.00	0.01	0.32	0.46	0.59	0.75	0.96	1.16	1.41	1.66	1.87	2.11	2.28	2.34	2.37	2.40	2.43	2.45	2.46
60	0.00	0.00	0.27	0.34	0.49	0.58	0.69	0.85	0.99	1.13	1.24	1.41	1.54	1.68	1.78	1.87	1.96	2.03	2.07
70	0.00	0.00	0.03	0.28	0.33	0.40	0.52	0.59	0.67	0.74	0.80	0.88	0.96	1.02	1.06	1.10	1.12	1.14	1.15
80	0.00	0.00	0.00	0.01	0.05	0.15	0.28	0.32	0.34	0.37	0.41	0.45	0.50	0.54	0.59	0.62	0.65	0.67	0.69
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.14	0.39	0.62	0.59	0.59	0.61	0.63	0.65	0.67	0.69	0.71	0.73	0.74	0.75	0.75
110	0.00	0.00	0.16	0.63	0.62	0.72	0.81	0.93	1.03	1.06	1.15	1.23	1.31	1.40	1.47	1.51	1.52	1.53	1.51
120	0.00	0.00	0.63	0.68	0.83	1.01	1.11	1.30	1.56	1.91	2.48	2.92	3.26	3.56	3.85	4.13	4.29	4.39	4.42
130	0.00	0.09	0.61	0.82	1.03	1.23	1.60	2.27	3.04	3.62	4.35	4.83	5.11	5.40	5.59	5.80	5.96	6.06	6.10
140	0.00	0.36	0.71	0.94	1.19	1.65	2.66	3.46	4.37	4.94	5.39	5.83	6.20	6.58	6.78	6.81	6.74	6.65	6.58
150	0.00	0.50	0.78	1.04	1.38	2.30	3.38	4.44	5.03	5.61	6.14	6.81	7.01	6.80	6.56	6.37	6.20	6.04	5.96
160	0.00	0.58	0.82	1.07	1.65	3.00	3.89	4.85	5.49	6.11	6.84	6.96	6.57	6.22	5.80	5.24	4.67	4.26	4.09
170	0.00	0.63	0.85	1.16	1.82	3.17	4.40	5.08	5.83	6.45	7.25	6.62	6.22	5.79	4.74	3.74	2.79	1.96	1.59
180	0.00	0.64	0.86	1.19	1.89	3.24	4.51	5.16	5.94	6.89	7.22	6.53	6.14	5.38	4.28	3.06	1.69	0.00	0.00

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.18V I:0.6883A P:5.324W PF:0.6349 Freq:59.97Hz Lamp Flux:32.1753x1 lm		
NAME: LED LANDSCAPE LIGHT	TYPE:Aluminum Path Light	WEIGHT:
SPEC.:5.5W 3000K 40°LENS	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-180	0.00	1.28	2.67	3.96	5.25	6.11	6.04	6.27	6.31	6.10	5.15	4.14	2.86	1.56	1.05	0.89	0.52	0.00	
-170	1.78	2.59	3.63	4.70	5.66	6.12	6.21	6.44	6.31	6.03	5.07	4.11	2.80	1.53	1.06	0.88	0.51	0.00	
-160	4.57	4.91	5.52	5.92	6.22	6.33	6.48	6.52	6.24	5.75	4.78	3.85	2.53	1.40	1.05	0.84	0.48	0.00	
-150	6.34	6.41	6.46	6.54	6.69	6.66	6.52	6.29	5.93	5.11	4.34	3.25	2.04	1.28	0.97	0.78	0.44	0.00	
-140	6.96	6.88	6.81	6.70	6.53	6.35	6.16	5.67	5.01	4.40	3.46	2.42	1.51	1.14	0.94	0.70	0.36	0.00	
-130	6.42	6.37	6.29	6.13	5.80	5.41	4.99	4.58	3.90	3.06	2.25	1.56	1.21	1.00	0.89	0.64	0.23	0.00	
-120	5.17	5.05	4.88	4.55	4.15	3.70	3.20	2.70	2.14	1.67	1.39	1.18	1.01	0.93	0.71	0.53	0.10	0.00	
-110	2.37	2.26	2.12	1.96	1.81	1.66	1.50	1.36	1.25	1.11	1.03	0.96	0.81	0.68	0.55	0.30	0.01	0.00	
-100	1.14	1.12	1.10	1.07	1.03	0.97	0.90	0.83	0.77	0.71	0.64	0.57	0.48	0.36	0.17	0.02	0.00	0.00	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.69	0.67	0.64	0.60	0.56	0.53	0.49	0.45	0.39	0.35	0.30	0.24	0.20	0.18	0.12	0.04	0.00	0.00	
-70	1.43	1.38	1.31	1.25	1.19	1.11	1.03	0.94	0.85	0.73	0.65	0.55	0.46	0.35	0.24	0.20	0.04	0.00	
-60	2.21	2.14	2.05	1.95	1.83	1.68	1.51	1.35	1.20	1.05	0.93	0.81	0.66	0.52	0.39	0.23	0.13	0.00	
-50	2.76	2.70	2.64	2.57	2.46	2.36	2.20	1.95	1.68	1.42	1.18	0.98	0.84	0.66	0.50	0.32	0.21	0.00	
-40	2.90	2.85	2.81	2.76	2.65	2.58	2.49	2.36	2.19	1.88	1.51	1.19	0.95	0.78	0.59	0.40	0.22	0.00	
-30	2.46	2.50	2.55	2.63	2.65	2.64	2.57	2.47	2.35	2.19	1.86	1.43	1.08	0.84	0.64	0.44	0.23	0.00	
-20	1.86	1.96	2.11	2.23	2.39	2.53	2.53	2.53	2.39	2.27	2.07	1.62	1.19	0.88	0.70	0.47	0.23	0.00	
-10	0.97	1.41	1.75	1.98	2.13	2.31	2.47	2.44	2.36	2.29	2.12	1.76	1.27	0.91	0.72	0.49	0.23	0.00	
0	0.30	0.97	1.61	1.87	2.08	2.18	2.40	2.36	2.34	2.24	2.10	1.79	1.27	0.90	0.72	0.49	0.23	0.00	
10	0.98	1.37	1.71	1.95	2.09	2.28	2.46	2.43	2.33	2.26	2.10	1.74	1.25	0.89	0.72	0.49	0.23	0.00	
20	1.82	1.89	2.03	2.13	2.30	2.50	2.52	2.48	2.32	2.21	2.03	1.58	1.16	0.86	0.70	0.47	0.23	0.00	
30	2.30	2.33	2.43	2.57	2.60	2.59	2.48	2.36	2.25	2.13	1.82	1.37	1.03	0.81	0.63	0.44	0.23	0.00	
40	2.84	2.78	2.69	2.62	2.50	2.42	2.33	2.23	2.09	1.81	1.43	1.12	0.90	0.76	0.59	0.39	0.23	0.00	
50	2.44	2.42	2.38	2.33	2.27	2.22	2.06	1.85	1.56	1.31	1.07	0.91	0.79	0.64	0.50	0.32	0.21	0.00	
60	2.03	1.96	1.86	1.74	1.63	1.49	1.34	1.18	1.05	0.95	0.85	0.77	0.64	0.52	0.39	0.24	0.13	0.00	
70	1.13	1.11	1.08	1.05	1.01	0.95	0.89	0.84	0.79	0.71	0.65	0.54	0.45	0.34	0.24	0.21	0.04	0.00	
80	0.68	0.65	0.63	0.59	0.56	0.52	0.48	0.44	0.39	0.34	0.30	0.25	0.25	0.21	0.13	0.04	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100	0.75	0.74	0.73	0.71	0.68	0.66	0.63	0.61	0.60	0.60	0.58	0.54	0.34	0.20	0.08	0.00	0.00	0.00	
110	1.51	1.49	1.45	1.39	1.32	1.24	1.16	1.08	1.03	0.97	0.91	0.83	0.69	0.62	0.54	0.23	0.00	0.00	
120	4.37	4.25	4.06	3.81	3.49	3.13	2.70	2.17	1.69	1.37	1.17	1.04	0.93	0.85	0.65	0.52	0.08	0.00	
130	6.07	5.99	5.84	5.64	5.41	5.07	4.69	4.15	3.49	2.74	1.93	1.36	1.09	0.94	0.83	0.62	0.20	0.00	
140	6.57	6.58	6.63	6.63	6.55	6.26	5.92	5.43	4.84	4.11	3.21	2.18	1.37	1.06	0.90	0.67	0.34	0.00	
150	6.04	6.16	6.24	6.36	6.41	6.51	6.47	6.22	5.74	4.96	4.15	3.08	1.89	1.20	0.94	0.75	0.43	0.00	
160	4.21	4.60	5.18	5.68	6.10	6.23	6.35	6.49	6.21	5.63	4.71	3.72	2.43	1.35	1.02	0.82	0.48	0.00	
170	1.85	2.60	3.49	4.58	5.54	6.06	6.17	6.39	6.32	5.98	5.02	4.05	2.75	1.50	1.04	0.87	0.51	0.00	
180	0.00	1.28	2.67	3.96	5.25	6.11	6.04	6.27	6.31	6.10	5.15	4.14	2.86	1.56	1.05	0.89	0.52	0.00	

H(β) Range:-90 - 90DEG
H(β) Interval: 0.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ADMIN
Test Date:2024-01-06

V(B) Range:-180 - 180DEG
V(B) Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.352
Humidity:65.0%
Test Distance:13.563m [K=1.0000]
Remarks: